

Datasheet for: 106877


Throttle check valve, Supply air throttle (»V«) G 1/4 i., G 1/4

Throttle check valve, Supply air throttle (»V«) Threaded connection G 1/4 i., G 1/4, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Type number	357.014-1/4
Article number	106877
EAN/barcode	 4047322181747
Your price	10,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	40.0 mm
C	22.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
Connection	G 1/4 IG
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK498
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/4
a/f	17 mm

Variants

Article number	Thread	Connection	a/f	Price
106877	G 1/4	G 1/4 IG	17 mm	10,54 € / Stk
106876	G 1/8	G 1/8 IG	14 mm	9,72 € / Stk
106875	M5	M5 IG	8 mm	9,72 € / Stk
106878	G 3/8	G 3/8 IG	20 mm	18,90 € / Stk

More Pictures

