


## Datasheet for: 134723


**Reducing nipple short, G 1 1/2 o., G 3/4 i., nickel-plated brass**

Reducing nipple short, G 1 1/2 o., G 3/4 i., AF 55, nickel-plated brass, Max. working pressure 25 bar, Max. operating temp. 150 °C . Suitable for air, water, oil, steam, etc.

Type number	MSN251K11234
Article number	134723
EAN/barcode	 4047322489690
Your price	14,08 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Female thread	G 3/4
L1	23.0 mm
L2	15.0 mm
Male thread	G 1 1/2
Material	Nickel-plated brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	HK774
a/f	55 mm

**Variants**

Article number	Male thread	Female thread	a/f	Price
134723	G 1 1/2	G 3/4	55 mm	14,08 € / Stk
100844	G 1	G 3/4	36 mm	4,81 € / Stk
100848	G 1 1/2	G 1 1/4	50 mm	11,17 € / Stk

## Variants

<i>Article number</i>	<i>Male thread</i>	<i>Female thread</i>	<i>a/f</i>	<i>Price</i>
134718	G 3/4	G 1/2	32 mm	3,55 € / Stk
134719	G 1	G 1/2	38 mm	5,52 € / Stk
134720	G 1	G 3/4	38 mm	6,15 € / Stk
134735	G 3	G 2 1/2	95 mm	92,88 € / Stk
134726	G 2	G 1	70 mm	27,32 € / Stk
134717	G 3/4	G 3/8	32 mm	3,38 € / Stk
134731	G 3	G 1	95 mm	85,80 € / Stk
134711	G 3/8	G 1/8	19 mm	1,07 € / Stk
134733	G 3	G 1 1/2	95 mm	90,56 € / Stk
134715	G 1/2	G 3/8	24 mm	2,06 € / Stk
134713	G 1/2	G 1/8	24 mm	1,93 € / Stk
134732	G 3	G 1 1/4	95 mm	88,77 € / Stk
134714	G 1/2	G 1/4	24 mm	1,98 € / Stk
134722	G 1 1/4	G 1	50 mm	10,22 € / Stk
134710	G 1/4	G 1/8	17 mm	0,84 € / Stk
134712	G 3/8	G 1/4	19 mm	1,16 € / Stk
134728	G 2	G 1 1/2	70 mm	29,30 € / Stk
134727	G 2	G 1 1/4	70 mm	27,32 € / Stk
134729	G 2 1/2	G 1 1/2	80 mm	38,07 € / Stk
134730	G 2 1/2	G 2	80 mm	82,00 € / Stk
134725	G 1 1/2	G 1 1/4	55 mm	20,93 € / Stk
134724	G 1 1/2	G 1	55 mm	20,93 € / Stk
134734	G 3	G 2	95 mm	91,02 € / Stk
134716	G 3/4	G 1/4	32 mm	2,98 € / Stk
134721	G 1 1/4	G 3/4	50 mm	11,59 € / Stk

## More Pictures

