


## Datasheet for: 133601


**Elbow2a 90°short Rp11/2 IT,Rp11/2 IT black malleable iron fitting**

Elbow 2a, 90°, short, Rp 1 1/2 IT, Rp 1 1/2 IT, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFB 2A-112-S
Article number	133601
EAN/barcode	 4047322479653
Your price	8,25 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK865
Standard	acc. ISO 7-1
thread	
Surface	Black
Thread	Rp 1 1/2

**Variants**

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133601	Rp 1 1/2	8,25 € / Stk
133602	Rp 2	12,78 € / Stk
133598	Rp 3/4	2,58 € / Stk
133597	Rp 1/2	1,79 € / Stk
133600	Rp 1 1/4	5,83 € / Stk
133599	Rp 1	3,87 € / Stk