


Datasheet for: 117924


Distributor, 2 quick-connect coupl. I.D. 7.2, G 1/4 ET, »R26EMS«

Distributor with 2 quick-connect couplings I.D. 7.2, »R26EMS«, Bright brass, G 1/4 ET, Operating pressure - 35 bar . 2-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside.

Type number	245.31-E
Article number	117924
EAN/barcode	 4047322222983
Your price	14,12 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Comprising distributor	Brass with a bare metal surface, G 3/8 IT
Connection	G 1/4 ET
Couplings	DN 7.2, brass with a bare metal surface, G 3/8 ET
Height	84.0 mm
Housing	Brass with a bare metal surface
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	35 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK534
Page No. AS	Web-Only
Page No. TS	TS007
Sealant	Industrial adhesives, medium strength
Securing	Industrial adhesives, medium strength
Width	89.0 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
117924	G 1/4 ET	14,12 € / Stk
117926	G 1/2 ET	17,32 € / Stk
117925	G 3/8 ET	14,12 € / Stk

More Pictures

