


**- Adjustable with slotted-head screwdriver -**

For regulation of a cylinder piston speed at both ends and control of flow rates.

Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly.

Compact type of construction, also ideal where space is restricted.



Operating pressure:

Max. 10 bar

Temperature range:

0 °C to +70 °C

Hollow bolt, pivoting arm, adjusting screw:

Nickel-plated brass

Valve trim:


Brass with a bare metal surface

Lip seal, O-ring:

NBR

Captive seals:

Polyamide (glass fibre-reinforced)



344.014-6



344.005-4

**Bidirectional flow control valves, air restriction at both ends (»B«), plug-in connector**

Type No.	Art. No.	Thread	For pipe mm	a/f mm	B mm	C mm
344.005-4	106979	M5	4	8	24.5	18.6
344.005-6	106980	M5	6	8	24.5	21.7
344.018-4	106981	G 1/8	4	14	32.0	20.6
344.018-6	106982	G 1/8	6	14	32.0	22.7
344.018-8	106983	G 1/8	8	14	32.0	23.7
344.014-6	106984	G 1/4	6	17	40.0	24.2
344.014-8	106985	G 1/4	8	17	40.0	24.7
344.014-10	106986	G 1/4	10	17	40.0	26.8
344.038-10	106987	G 3/8	10	20	50.0	28.8

**Nominal flow:**

