


Datasheet for: 110309



Angle connector POM, for hose exterior Ø 18 mm

Angle connector POM, for hose exterior Ø 18 mm, Working pressure max. 10 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	68.018
Article number	110309
EAN/barcode	 4047322112291
Your price	8,28 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	18 mm
L1	59.7 mm
L2	59.7 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	10 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK940

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Max. working pressure</i>	<i>Price</i>
110309	18 mm	10 bar	8,28 € / Stk
110302	4 mm	16 bar	2,22 € / Stk
110303	5 mm	16 bar	2,22 € / Stk
110304	6 mm	16 bar	2,39 € / Stk
110305	8 mm	16 bar	2,67 € / Stk
110306	10 mm	10 bar	3,63 € / Stk
110307	12 mm	10 bar	4,82 € / Stk
110308	15 mm	10 bar	7,08 € / Stk
110310	22 mm	10 bar	10,91 € / Stk
110311	28 mm	10 bar	18,53 € / Stk

More Pictures

