

Datasheet for: 141513

Quick-connect coupling I.D. 7.8, Steel, R 3/8 ET



Quick-connect coupling I.D. 7.8, Steel, R 3/8 ET, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . Single-sided blocking, high quality and robust quick connect coupling for high flow values. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.

Type number	244.62-E
Article number	141513
EAN/barcode	 4047322568050
Your price	14,39 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	R 3/8 ET
DN	7.8
Flow rate	2000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Galvanised steel
Length	61.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK549
Page No. SK	SK031
Page No. TS	TS008
Sealant	NBR

Sleeve	Galvanised steel
Spring	Stainless steel
Threaded piece	Galvanised steel
Valve	Die-cast zinc (zamac)
a/f	19 mm

Variants

Article number	Connection	Length	a/f	Price
141513	R 3/8 ET	61.0 mm	19 mm	14,39 € / Stk
141514	R 1/2 ET	55.0 mm	22 mm	15,35 € / Stk
141512	R 1/4 ET	59.0 mm	19 mm	14,39 € / Stk

More Pictures

