


Datasheet for: 108962


Push-in L-fitting »metallica«, G 1/2 o., for hose exterior Ø 12

Push-in L-fitting »metallica«, G 1/2 o., for hose exterior Ø 12 mm, Working pressure max. 16 bar, nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	863.012-12
Article number	108962
EAN/barcode	 4047322391214
Your price	14,50 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	12 mm
L1	34.5 mm
L2	42.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK715
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 1/2
a/f	24 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
108962	G 1/2	12 mm	24 mm	14,50 € / Stk
108958	G 1/4	10 mm	17 mm	6,71 € / Stk
108955	G 1/8	8 mm	14 mm	5,20 € / Stk
108957	G 1/4	8 mm	17 mm	6,13 € / Stk
108953	G 1/8	4 mm	14 mm	5,13 € / Stk
108956	G 1/4	6 mm	17 mm	6,10 € / Stk
108954	G 1/8	6 mm	14 mm	5,13 € / Stk
108961	G 3/8	12 mm	19 mm	11,76 € / Stk
108959	G 3/8	8 mm	19 mm	9,58 € / Stk
108952	M5	6 mm	8 mm	4,95 € / Stk
108951	M5	5 mm	8 mm	4,71 € / Stk
108950	M5	4 mm	8 mm	4,61 € / Stk
108960	G 3/8	10 mm	19 mm	10,25 € / Stk

More Pictures

