


Datasheet for: 107299


Quick-connect coupling I.D. 7.2, Sleeve 13 mm, rotating

Quick-connect coupling I.D. 7.2, nickel-plated brass, Sleeve 13 mm rotating, Operating pressure - 35 bar, Temp. °C to 70 °C . Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Type number	243.404-N
Article number	107299
EAN/barcode	 4047322277235
Your price	14,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Stem 13 mm, swivel type
DN	7.2
Flow rate	1000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Nickel-plated brass
Length	74.0 mm
Locking pins	Stainless steel 1.4034
Max. ambient temperature	70 °C
Max. medium temperature	70 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK541
Page No. SK	SK022
Retaining ring	Stainless steel 1.4310
Sealant	NBR
Sleeve	Nickel-plated brass
Spring	Stainless steel 1.4310

Valve body

Brass with a bare metal surface

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107299	Stem 13 mm, swivel type	14,54 € / Stk
107298	Stem 10 mm, swivel type	14,54 € / Stk
107295	Stem 6 mm, swivel type	14,54 € / Stk
107296	Stem 8 mm, swivel type	14,54 € / Stk
107297	Stem 9 mm, swivel type	14,54 € / Stk

More Pictures