


Datasheet for: 107495


Quick-connect coupling I.D. 5, locking on both sides, G 1/4 IT

Quick-connect coupling I.D. 5, locking on both sides, Bright brass, G 1/4 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C . Both the coupling and the self-sealing plug are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping. Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

Type number	243.21-B
Article number	107495
EAN/barcode	 4047322058964
Your price	6,15 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 1/4 IT
DN	5
Flow rate	310 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	38.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK557
Page No. SK	SK039
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface

Spring
 Valve body
 a/f

Stainless steel
 Brass with a bare metal surface
 17 mm

Variants

Article number	Connection	a/f	Price
107495	G 1/4 IT	17 mm	6,15 € / Stk
107494	G 1/8 IT	14 mm	6,15 € / Stk

More Pictures

