


Datasheet for: 133653


**Fitting elbow 98 IT/ET Rp11/4, R11/4 black malleable iron fitting**

Fitting elbow 98, conical sealing IT/ET Rp 1 1/4, R 1 1/4, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFV 98-114-S
Article number	133653
EAN/barcode	 4047322480482
Your price	14,55 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK867
Standard thread	acc. ISO 7-1
Surface	Black
Thread 1	Rp 1 1/4
Thread 2	R 1 1/4

**Variants**

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Price</i>
133653	Rp 1 1/4	R 1 1/4	14,55 € / Stk
133651	Rp 3/4	R 3/4	7,61 € / Stk
133650	Rp 1/2	R 1/2	5,66 € / Stk
133654	Rp 2	R 2	28,13 € / Stk
133652	Rp 1	R 1	8,90 € / Stk