

Datasheet for: 107096


Quick-connect coupling I.D. 2.7 nickel-plated brass, push-in 4 mm

Quick-connect coupling I.D. 2.7 nickel-plated brass, push-in connection 4 mm, Operating pressure - 35 bar, Temp. -20°C to 100°C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

Type number	243.08/10-N
-------------	-------------

Article number	107096
----------------	--------

EAN/barcode	 4047322207522
-------------	--

Your price	10,94 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	4 mm
DN	2.7
Flow rate	165 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Nickel-plated brass
Length	35.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK520
Page No. SK	SK006
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Nickel-plated brass

Spring
Valve body
a/f

Stainless steel
Nickel-plated brass
10 mm

More Pictures

