


Datasheet for: 112905


Bracket 92, 90°, IT/ET, Rp/R 1 1/2, black malleable cast iron

Bracket 92, 90°, IT/ET, Rp/R 1 1/2, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 92-112
Article number	112905
EAN/barcode	 4047322252263
Your price	6,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK856
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp/R 1 1/2

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112905	Rp/R 1 1/2	6,22 € / Stk
112900	Rp/R 3/8	1,41 € / Stk
112902	Rp/R 3/4	1,61 € / Stk
112901	Rp/R 1/2	1,11 € / Stk
112906	Rp/R 2	8,56 € / Stk
112903	Rp/R 1	2,51 € / Stk
112904	Rp/R 1 1/4	4,53 € / Stk
112899	Rp/R 1/4	1,41 € / Stk
112907	Rp/R 2 1/2	20,99 € / Stk
112908	Rp/R 3	28,75 € / Stk