


Datasheet for: 107095

Quick-connect coupling I.D. 2.7, nickel-plated brass, Hose 6x4


Quick-connect coupling I.D. 2.7, nickel-plated brass, Hose connection 6x4, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

Type number	243.08/9-N
Article number	107095
EAN/barcode	 4047322058087
Your price	10,98 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	Hose connection 6x4
DN	2.7
Flow rate	165 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Nickel-plated brass
Length	34.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK520
Page No. SK	SK006
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Nickel-plated brass

Spring
Valve bodyStainless steel
Nickel-plated brass**Variants**

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107095	Hose connection 6x4	10,98 € / Stk
107093	Hose connection 4x3	8,05 € / Stk
107094	Hose connection 5x3	8,05 € / Stk

More Pictures