


Datasheet for: 101702


Standard pressure gauge, radial bottom, G 1/4, -1200/0 mbar, Ø 63

Standard pressure gauge, Single scale bar, Connection radial bottom, G 1/4, Goods class 2.5, Measurement range -1200/0 mbar, Ø 63 . Bourdon-tube pressure gauge in standard design. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	6300-K
Article number	101702
EAN/barcode	 4047322107099
Your price	8,45 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	2.5
Connection	G 1/4
Connection position	radial on bottom
Diameter	63 mm
Front glass	Transparent plastic
Housing	Plastic
Lower / Upper range limit	Vacuum
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. mbar	0.0
Measuring range min. mbar	-1200.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK197
Scale graduation in the mbar area	50.0 mbar
Type	111.10

Variants

Article number	Accuracy class	Measuring range min. bar	Measuring range max. bar	Diameter	Connection	Price
101702	2.5			63 mm	G 1/4	8,45 € / Stk
101680	1.6	-1.0	0.0	40 mm	G 1/8	8,06 € / Stk
101681	1.6	0.0	1.6	40 mm	G 1/8	8,06 € / Stk
101682	1.6	0.0	2.5	40 mm	G 1/8	8,06 € / Stk
101683	1.6	0.0	4.0	40 mm	G 1/8	8,06 € / Stk
101684	1.6	0.0	6.0	40 mm	G 1/8	8,06 € / Stk
101685	1.6	0.0	10.0	40 mm	G 1/8	8,06 € / Stk
101686	1.6	0.0	16.0	40 mm	G 1/8	8,06 € / Stk
101687	2.5	0.0	25.0	40 mm	G 1/8	8,06 € / Stk
101688	1.6	0.0	40.0	40 mm	G 1/8	8,06 € / Stk
101689	1.6	-1.0	0.0	50 mm	G 1/4	8,45 € / Stk
101690	1.6	0.0	1.0	50 mm	G 1/4	8,45 € / Stk
101691	1.6	0.0	1.6	50 mm	G 1/4	8,45 € / Stk
101692	1.6	0.0	2.5	50 mm	G 1/4	8,45 € / Stk
101693	1.6	0.0	4.0	50 mm	G 1/4	8,45 € / Stk
101694	1.6	0.0	6.0	50 mm	G 1/4	8,45 € / Stk
101695	1.6	0.0	10.0	50 mm	G 1/4	8,45 € / Stk
101696	1.6	0.0	16.0	50 mm	G 1/4	8,45 € / Stk
101697	1.6	0.0	25.0	50 mm	G 1/4	8,45 € / Stk
101698	1.6	0.0	40.0	50 mm	G 1/4	8,45 € / Stk
101699	1.6	0.0	60.0	50 mm	G 1/4	10,10 € / Stk
101700	1.6	0.0	100.0	50 mm	G 1/4	10,10 € / Stk
101701	2.5	0.0	160.0	50 mm	G 1/4	10,10 € / Stk
101703	1.6	-1.0	0.0	63 mm	G 1/4	8,45 € / Stk
101704	1.6	-1.0	0.6	63 mm	G 1/4	8,45 € / Stk
101705	1.6	-1.0	1.5	63 mm	G 1/4	8,45 € / Stk
101706	1.6	-1.0	3.0	63 mm	G 1/4	8,45 € / Stk
101707	2.5	-1.0	5.0	63 mm	G 1/4	8,45 € / Stk
101708	1.6	-1.0	9.0	63 mm	G 1/4	8,45 € / Stk
101709	1.6	-1.0	15.0	63 mm	G 1/4	8,45 € / Stk
101710	1.6	0.0	0.6	63 mm	G 1/4	8,45 € / Stk

Variants

Article number	Accuracy class	Measuring range min. bar	Measuring range max. bar	Diameter	Connection	Price
101711	1.6	0.0	1.0	63 mm	G 1/4	8,45 € / Stk
101712	1.6	0.0	1.6	63 mm	G 1/4	8,45 € / Stk
101713	1.6	0.0	2.5	63 mm	G 1/4	8,45 € / Stk
101714	1.6	0.0	4.0	63 mm	G 1/4	8,45 € / Stk
101715	1.6	0.0	6.0	63 mm	G 1/4	8,45 € / Stk
101716	1.6	0.0	10.0	63 mm	G 1/4	8,45 € / Stk
101717	1.6	0.0	16.0	63 mm	G 1/4	8,45 € / Stk
101718	1.6	0.0	25.0	63 mm	G 1/4	8,45 € / Stk
101719	1.6	0.0	40.0	63 mm	G 1/4	8,45 € / Stk
101720	1.6	0.0	60.0	63 mm	G 1/4	10,10 € / Stk
101721	1.6	0.0	100.0	63 mm	G 1/4	10,10 € / Stk
101722	1.6	0.0	160.0	63 mm	G 1/4	10,10 € / Stk
101723	1.6	0.0	250.0	63 mm	G 1/4	10,10 € / Stk
101724	1.6	0.0	315.0	63 mm	G 1/4	10,10 € / Stk
101725	1.6	0.0	400.0	63 mm	G 1/4	10,10 € / Stk