


Datasheet for: 133568


Bracket 90°, red. IT/IT Rp2 1/2,Rp1 1/2,black malleable cast iron

Bracket 90°, red. IT/IT Rp 2 1/2, Rp 1 1/2, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, ISO 7-1 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 90-212112
Article number	133568
EAN/barcode	 4047322482172
Your price	11,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK856
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread 1	Rp 2 1/2
Thread 2	Rp 1 1/2

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Price</i>
133568	Rp 2 1/2	Rp 1 1/2	11,07 € / Stk
133566	Rp 1 1/2	Rp 1 1/4	7,23 € / Stk
133563	Rp 1	Rp 3/4	2,65 € / Stk
133562	Rp 1	Rp 1/2	2,38 € / Stk
133561	Rp 3/4	Rp 1/2	1,64 € / Stk
133564	Rp 1 1/4	Rp 1	4,07 € / Stk
133565	Rp 1 1/2	Rp 1/2	7,19 € / Stk
133567	Rp 2	Rp 1	10,28 € / Stk
133560	Rp 1/2	Rp 3/8	1,46 € / Stk