


Datasheet for: 103809


Throttle valve, in block shape, Anodised aluminium, G 1/8

Throttle valve, in block shape, Anodised aluminium, Operating temperature -10 °C to 70 °C, G 1/8, PN max. 10 bar . Straight-way valves with restricted flow in both directions.

Type number	225.53
Article number	103809
EAN/barcode	 4047322040631
Your price	11,09 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	34.0 mm
C	16.0 mm
E	24.0 mm
Housing	Anodized aluminium
I	15.0 mm
Internal parts	Brass
L	4.5 mm
M	16.4 mm
Max. operating pressure	10 bar
Max. operating temperature	70 °C
Min. operating temperature	-10 °C
Page No.	HK352
Sealant	NBR
Thread	G 1/8
Thread for panel mounting	M12x0.75
a/f	15 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>a/f</i>	<i>Thread for panel mounting</i>	<i>Price</i>
103809	G 1/8	15 mm	M12x0.75	11,09 € / Stk
103810	G 1/4	22 mm	M18x1.5	12,81 € / Stk
103811	G 3/8	22 mm	M18x1.5	19,81 € / Stk
103812	G 1/2	26 mm	M22x1.5	22,48 € / Stk

More Pictures

