

Datasheet for: 107075


Quick-connect coupling I.D. 2.7, bright brass, Hose connect. 4x3

Quick-connect coupling I.D. 2.7, bright brass, Hose connection 4x3, Operating pressure 0-35 bar, Med./ambient temp. -20°C to 100°C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

| | |
|----------------|--|
| Type number | 243.08/7 |
| Article number | 107075 |
| EAN/barcode |  4047322058032 |
| Your price | 6,30 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|--|
| Ball | Stainless steel |
| Connection | Hose connection 4x3 |
| DN | 2.7 |
| Flow rate | 165 l/min (air) |
| Flow rate measurement | at 6 bar and $\Delta_p = 0.5$ bar |
| Housing | Brass with a bare metal surface |
| Length | 34.0 mm |
| Max. ambient temperature | 100 °C |
| Max. medium temperature | 100 °C |
| Min. ambient temperature | -20 °C |
| Min. medium temperature | -20 °C |
| Operating pressure | to 35 bar, maximum static working pressure (non-pulsating) |
| Page No. | HK518 |
| Page No. SK | SK005 |
| Retaining ring | Stainless steel |
| Sealant | NBR |
| Sleeve | Brass with a bare metal surface |

Spring
Valve body

Stainless steel
Brass with a bare metal surface

Variants

| Article number | Connection | Price |
|----------------|---------------------|--------------|
| 107075 | Hose connection 4x3 | 6,30 € / Stk |
| 107076 | Hose connection 5x3 | 6,30 € / Stk |
| 107077 | Hose connection 6x4 | 6,30 € / Stk |

More Pictures

