

## Datasheet for: 107274


**Ceiling bracket with quick-connect coupling I.D. 7.2, G 1/2 IT**

Ceiling bracket with quick-connect coupling I.D. 7.2, Bright brass, G 1/2 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C . 1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Type number	DW 267-K
Article number	107274
EAN/barcode	 4047322368230
Your price	11,09 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Comprising distributor	2 x G 1/2 IT
Connection	G 1/2 IT
Couplings	DN 7.2, brass with a bare metal surface, G 1/2 ET
Height	46.0 mm
Housing	Brass with a bare metal surface
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	35 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK535
Page No. SK	SK020
Sealant	Industrial adhesives, medium strength
Securing	Industrial adhesives, medium strength
Width	45.0 mm

## Variants

Article number	Connection	Comprising distributor	Couplings	Price
107274	G 1/2 IT	2 x G 1/2 IT	DN 7.2, brass with a bare metal surface, G 1/2 ET	11,09 € / Stk
107273	G 3/8 IT	2 x G 3/8 IT	DN 7.2, brass with a bare metal surface, G 3/8 ET	10,05 € / Stk

## More Pictures

