

Datasheet for: 110805



Angled screw-in fitting G 3/8 o., for hose 8/10 mm, PA

Angled screw-in fitting G 3/8 o., for hose 8/10 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.73
-------------	--------

Article number	110805
----------------	--------

EAN/barcode



4047322028035

Your price	6,32 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	8/10 mm
Knurled nut	Polypropylene (PP)
L1	36.0 mm
L2	29.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK742
Screw fitting body	Polyamide (PA)
Thread	G 3/8

Variants

Article number	Thread	For hose	Price
110805	G 3/8	8/10 mm	6,32 € / Stk

Variants

Article number	Thread	For hose	Price
110795	G 1/8	4/6 mm	1,63 € / Stk
110796	G 1/8	6/8 mm	2,92 € / Stk
110797	G 1/8	8/10 mm	4,15 € / Stk
110798	G 1/8	9/12 mm	10,85 € / Stk
110799	G 1/4	4/6 mm	2,08 € / Stk
110800	G 1/4	6/8 mm	3,19 € / Stk
110801	G 1/4	8/10 mm	5,24 € / Stk
110802	G 1/4	9/12 mm	11,05 € / Stk
110803	G 3/8	4/6 mm	3,78 € / Stk
110804	G 3/8	6/8 mm	4,01 € / Stk
110806	G 3/8	9/12 mm	11,58 € / Stk
110807	G 1/2	4/6 mm	4,39 € / Stk
110808	G 1/2	6/8 mm	5,27 € / Stk
110809	G 1/2	8/10 mm	6,39 € / Stk
110810	G 1/2	9/12 mm	13,78 € / Stk

More Pictures

