


## Datasheet for: 141010


**Strainer nickel-plated brass, G 3/8, DN 10, mesh width 0.05 mm**

Dirt strainer, nickel-plated brass, Sieve insert mesh width 0.05 mm, Operating temp. -20°C to 110°C, G 3/8, DN 10, PN max. 20 bar . Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

Type number	60-2 N-0,05
Article number	141010
EAN/barcode	 4047322547369
Your price	8,50 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

C	40.0 mm
DN	10.0
Head piece	Nickel-plated brass
Housing	Nickel-plated brass
L	55.0 mm
Max. operating pressure	20 bar
Max. operating temperature	110 °C
Mesh size	0.05 mm
Min. operating temperature	-20 °C
Page No.	HK370
Screen	Stainless steel
Sealant	NBR O-ring
Standard thread	G thread acc. to ISO 228-1, tolerance class B
Thread	G 3/8
a/f 1	21.0 mm
a/f 2	20.0 mm

## Variants

Article number	Thread	DN	a/f 1	a/f 2	Price
141010	G 3/8	10.0	21.0 mm	20.0 mm	8,50 € / Stk
141012	G 3/4	20.0	31.0 mm	27.0 mm	13,70 € / Stk
141016	G 2	50.0	67.0 mm	46.0 mm	63,43 € / Stk
141009	G 1/4	8.0	18.0 mm	20.0 mm	8,50 € / Stk
141015	G 1 1/2	40.0	54.0 mm	38.0 mm	38,70 € / Stk
141013	G 1	25.0	38.0 mm	32.0 mm	20,38 € / Stk
141014	G 1 1/4	32.0	47.0 mm	36.0 mm	29,85 € / Stk
141011	G 1/2	15.0	25.0 mm	20.0 mm	8,92 € / Stk

## More Pictures

