

Datasheet for: 106998


Throttle valve, Both sides throttling (»B«) quick connector

Throttle valve, Both sides throttling (»B«) quick connector
 Hose 8/6, G 1/8, PN max. 10 bar, Temperature °C to 70 °C .
 For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	337.018-8
-------------	-----------

Article number	106998
----------------	--------

EAN/barcode	
-------------	--



4047322180603

Your price	11,18 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	42.0 mm
C	25.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	8 / 6 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK503
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
a/f	14 mm

Variants

Article number	Thread	For hose	a/f	Price
106998	G 1/8	8 / 6 mm	14 mm	11,18 € / Stk
106993	M5	4 / 2.5 mm	8 mm	12,35 € / Stk
106994	M5	5 / 3 mm	8 mm	11,76 € / Stk
106995	M5	6 / 4 mm	8 mm	11,76 € / Stk
106996	G 1/8	5 / 3 mm	14 mm	11,18 € / Stk
106997	G 1/8	6 / 4 mm	14 mm	11,18 € / Stk
106999	G 1/4	6 / 4 mm	17 mm	12,81 € / Stk
107000	G 1/4	8 / 6 mm	17 mm	12,81 € / Stk
107001	G 1/4	10 / 8 mm	17 mm	13,29 € / Stk

More Pictures

