


Datasheet for: 106944


Throttle check valve, Discharge throttle (»C«) G 1/8 IT, G 1/8

Throttle check valve, Discharge throttle (»C«) Threaded connection G 1/8 IT, G 1/8, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

| | |
|----------------|--|
| Type number | 333.018-1/8 |
| Article number | 106944 |
| EAN/barcode |  4047322180375 |
| Your price | 11,23 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|------------------------------------|
| Adjusting screw | Nickel-plated brass |
| B | 42.0 mm |
| C | 16.0 mm |
| Captive seals | Polyamide (glass fibre-reinforced) |
| Connection | G 1/8 female thread |
| Hollow bolt | Nickel-plated brass |
| Internal parts | Brass with a bare metal surface |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Page No. | HK501 |
| Pivoting arm | Nickel-plated brass |
| Sealant | NBR |
| Thread | G 1/8 |
| a/f | 14 mm |

Variants

| Article number | Thread | Connection | a/f | Price |
|----------------|--------|---------------------|-------|---------------|
| 106944 | G 1/8 | G 1/8 female thread | 14 mm | 11,23 € / Stk |
| 106943 | M5 | M5 female thread | 8 mm | 11,76 € / Stk |
| 106945 | G 1/4 | G 1/4 female thread | 17 mm | 13,40 € / Stk |
| 106946 | G 3/8 | G 3/8 female thread | 20 mm | 21,09 € / Stk |
| 106947 | G 1/2 | G 1/2 female thread | 26 mm | 30,65 € / Stk |

More Pictures

