Datasheet for: 101244

Standard pressure gauge, rear centric, G 1/4, - 10 bar/145 psi

Standard pressure gauge, Double scale, Connection, rear, centr., G 1/4, Goods class 1.6, Measurement range 0-10 bar/145 psi, Ø 63 . Bourdon-tube pressure gauge in standard design. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	217-KD
Article number	101244
EAN/barcode	4047322034852
Your price	8,57 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Connection	G 1/4
Connection position	rear, centrical
Description	Pressure gauge Ø 63 mm, G 1/4 ET, - 10 bar/145 psi
Diameter	63 mm
Front glass	Transparent plastic
Housing	Plastic
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	10.0
Measuring range max. psi	145.0
Measuring range min. bar	0.0
Measuring range min. psi	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK196
Page No. TS	TS004

Scale graduation in the bar area	0.5 bar
Type	111.12

Variants

Article number	Measuring range max. bar	Measuring range max. psi	Diameter	Connection	Price
101244	10.0	145.0	63 mm	G 1/4	8,57 € / Stk
101670	2.5	36.0	40 mm	G 1/8	8,39 € / Stk
101671	4.0	58.0	40 mm	G 1/8	8,39 € / Stk
101533	6.0	86.0	40 mm	G 1/8	8,39 € / Stk
101672	10.0	145.0	40 mm	G 1/8	8,39 € / Stk
101534	16.0	230.0	40 mm	G 1/8	8,39 € / Stk
101673	25.0	360.0	40 mm	G 1/8	8,39 € / Stk
101674	2.5	36.0	50 mm	G 1/4	8,57 € / Stk
101675	4.0	58.0	50 mm	G 1/4	8,57 € / Stk
101676	6.0	86.0	50 mm	G 1/4	8,57 € / Stk
101677	10.0	145.0	50 mm	G 1/4	8,57 € / Stk
101678	16.0	230.0	50 mm	G 1/4	8,57 € / Stk
101679	25.0	360.0	50 mm	G 1/4	8,57 € / Stk
101222	2.5	36.0	63 mm	G 1/4	8,57 € / Stk
101223	4.0	58.0	63 mm	G 1/4	8,57 € / Stk
101224	6.0	86.0	63 mm	G 1/4	8,57 € / Stk
101398	16.0	230.0	63 mm	G 1/4	8,57 € / Stk
101462	25.0	360.0	63 mm	G 1/4	8,57 € / Stk