

## Datasheet for: 101674


**Standard pressure gauge, rear centric, G 1/4, - 2.5 bar/36 psi**

Standard pressure gauge, Double scale, Connection, rear, centr., G 1/4, Goods class 1.6, Measurement range 0-2.5 bar/36 psi, Ø 50 . Bourdon-tube pressure gauge in standard design. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	203-KD
Article number	101674
EAN/barcode	 4047322033893
Your price	8,57 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Accuracy class	1.6
Connection	G 1/4
Connection position	rear, central
Diameter	50 mm
Front glass	Transparent plastic
Housing	Plastic
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	2.5
Measuring range max. psi	36.0
Measuring range min. bar	0.0
Measuring range min. psi	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK196
Scale graduation in the bar area	0.1 bar

Type

111.12

**Variants**

<i>Article number</i>	<i>Measuring range max. bar</i>	<i>Measuring range max. psi</i>	<i>Diameter</i>	<i>Connection</i>	<i>Price</i>
101674	2.5	36.0	50 mm	G 1/4	8,57 € / Stk
101670	2.5	36.0	40 mm	G 1/8	8,39 € / Stk
101671	4.0	58.0	40 mm	G 1/8	8,39 € / Stk
101533	6.0	86.0	40 mm	G 1/8	8,39 € / Stk
101672	10.0	145.0	40 mm	G 1/8	8,39 € / Stk
101534	16.0	230.0	40 mm	G 1/8	8,39 € / Stk
101673	25.0	360.0	40 mm	G 1/8	8,39 € / Stk
101675	4.0	58.0	50 mm	G 1/4	8,57 € / Stk
101676	6.0	86.0	50 mm	G 1/4	8,57 € / Stk
101677	10.0	145.0	50 mm	G 1/4	8,57 € / Stk
101678	16.0	230.0	50 mm	G 1/4	8,57 € / Stk
101679	25.0	360.0	50 mm	G 1/4	8,57 € / Stk
101222	2.5	36.0	63 mm	G 1/4	8,57 € / Stk
101223	4.0	58.0	63 mm	G 1/4	8,57 € / Stk
101224	6.0	86.0	63 mm	G 1/4	8,57 € / Stk
101244	10.0	145.0	63 mm	G 1/4	8,57 € / Stk
101398	16.0	230.0	63 mm	G 1/4	8,57 € / Stk
101462	25.0	360.0	63 mm	G 1/4	8,57 € / Stk