


## Datasheet for: 107936


**Tempered plug-in nipple DN 6, with blocking valve, ET, M14x1.5**

Tempered plug-in nipple DN 6, with blocking valve, ET, Brass 2.0401, M14x1.5, Operating pressure max. 15 bar, Temp. -20°C to 160°C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.622
Article number	107936
EAN/barcode	 4047322258289
Your price	6,39 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Length	29.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK616
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
Thread	M14x1.5
a/f	15 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>Price</i>
107936	M14x1.5	Brass 2.0401	6,39 € / Stk
107937	G 1/4	Nickel-plated brass	6,39 € / Stk