

## Datasheet for: 110809


**Angled screw-in fitting G 1/2 o., for hose 8/10 mm, PA**

Angled screw-in fitting G 1/2 o., for hose 8/10 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.83
Article number	110809
EAN/barcode	 4047322028134
Your price	6,39 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Clamping ring	Polypropylene (PP)
For hose	8/10 mm
Knurled nut	Polypropylene (PP)
L1	39.0 mm
L2	31.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK742
Screw fitting body	Polyamide (PA)
Thread	G 1/2

**Variants**

Article number	Thread	For hose	Price
110809	G 1/2	8/10 mm	6,39 € / Stk

## Variants

Article number	Thread	For hose	Price
110795	G 1/8	4/6 mm	1,63 € / Stk
110796	G 1/8	6/8 mm	2,92 € / Stk
110797	G 1/8	8/10 mm	4,15 € / Stk
110798	G 1/8	9/12 mm	10,85 € / Stk
110799	G 1/4	4/6 mm	2,08 € / Stk
110800	G 1/4	6/8 mm	3,19 € / Stk
110801	G 1/4	8/10 mm	5,24 € / Stk
110802	G 1/4	9/12 mm	11,05 € / Stk
110803	G 3/8	4/6 mm	3,78 € / Stk
110804	G 3/8	6/8 mm	4,01 € / Stk
110805	G 3/8	8/10 mm	6,32 € / Stk
110806	G 3/8	9/12 mm	11,58 € / Stk
110807	G 1/2	4/6 mm	4,39 € / Stk
110808	G 1/2	6/8 mm	5,27 € / Stk
110810	G 1/2	9/12 mm	13,78 € / Stk

## More Pictures

