


Datasheet for: 107883


Safety jaw coupling with hose connection, I.D. 13 (1/2"), DN 10

Safety jaw coupling with hose connection, I.D. 13 (1/2"), DN 10, Malleable cast iron, Operating pressure max. 16 bar . Universal standard coupling in safety design according to DIN 3238 for absolutely secure compressed air lines on construction sites or in industry. Easy to couple, secured against accidental opening: just screw the ring tight after coupling! - Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - Large bore for increased flow rate

Type number	KT 13 S
Article number	107883
EAN/barcode	 4047322260121
Your price	15,02 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	10.0
For hose I.D.	13 (1/2")
H	63.0 mm
L	87.2 mm
Material	Malleable iron
Max. operating pressure	16 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK613
Page No. SF	SF078
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Price</i>
107883	10.0	13 (1/2")	15,02 € / Stk
107885	19.0	25 (1")	15,02 € / Stk
107884	15.0	19 (3/4")	15,02 € / Stk