


Datasheet for: 107884


Safety jaw coupling with hose connection, I.D. 19 (3/4\"/>

Safety jaw coupling with hose connection, I.D. 19 (3/4\"/>
 15, Malleable cast iron, Operating pressure max. 16 bar .
 Universal standard coupling in safety design according to
 DIN 3238 for absolutely secure compressed air lines on
 construction sites or in industry. Easy to couple, secured
 against accidental opening: just screw the ring tight after
 coupling! - Robust couplings with malleable iron head, steel
 stem with special profile, zinc plated and yellow chromated -
 Chrome VI-free, with double safety lock - Large bore for
 increased flow rate

Type number	KT 19 S
Article number	107884
EAN/barcode	 4047322260138
Your price	15,02 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	15.0
For hose I.D.	19 (3/4\"/>
H	63.0 mm
L	88.7 mm
Material	Malleable iron
Max. operating pressure	16 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK613
Page No. SF	SF078
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Price</i>
107884	15.0	19 (3/4")	15,02 € / Stk
107883	10.0	13 (1/2")	15,02 € / Stk
107885	19.0	25 (1")	15,02 € / Stk