


## Datasheet for: 107911


**Tempered coupling DN6, Taps 9 mm, Blocking valve, Sleeve straight**

Tempered coupling DN 6, Taps 9 mm, Blocking valve, Brass, Hose sleeve straight, Operating press. max. 15 bar, Temp. -20°C to 160°C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.01
Article number	107911
EAN/barcode	 4047322257961
Your price	11,45 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Hose connection	9 mm
Hose stem type	straight
Length	53.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK615
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel

## Variants

<i>Article number</i>	<i>Hose stem type</i>	<i>Price</i>
107911	straight	11,45 € / Stk
107912	45°	16,54 € / Stk
107913	90°	16,54 € / Stk