


Datasheet for: 107170


Quick-connect coupling I.D. 5, nickel-plated brass, Hose 8x6

Quick-connect coupling I.D. 5, nickel-plated brass, Hose connection 8x6, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

| | |
|----------------|--|
| Type number | 243.28-N |
| Article number | 107170 |
| EAN/barcode |  4047322059459 |
| Your price | 6,53 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|--|
| Ball | Stainless steel |
| Connection | Hose connection 8x6 |
| DN | 5 |
| Flow rate | 560 l/min (air) |
| Flow rate measurement | at 6 bar and $\Delta_p = 0.5$ bar |
| Housing | Nickel-plated brass |
| Length | 43.0 mm |
| Max. ambient temperature | 100 °C |
| Max. medium temperature | 100 °C |
| Min. ambient temperature | -20 °C |
| Min. medium temperature | -20 °C |
| Operating pressure | to 35 bar, maximum static working pressure (non-pulsating) |
| Page No. | HK528 |
| Page No. SK | SK012 |
| Retaining ring | Stainless steel |
| Sealant | NBR |
| Sleeve | Nickel-plated brass |
| Spring | Stainless steel |

Valve body
a/f

Nickel-plated brass
14 mm

Variants

| Article number | Connection | Price |
|----------------|---------------------|--------------|
| 107170 | Hose connection 8x6 | 6,53 € / Stk |
| 107169 | Hose connection 6x4 | 6,53 € / Stk |

More Pictures

