


## Datasheet for: 107498


**Quick-connect coupl. I.D. 5, locking on both sides, Sleeve I.D. 9**

Quick-connect coupling I.D. 5, locking on both sides, Bright brass, Sleeve I.D. 9, Operat. pressure 0-35 bar, Temp. -20°C to 100°C . Both the coupling and the self-sealing plug are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping. Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

Type number	243.26/9-B
Article number	107498
EAN/barcode	 4047322059299
Your price	6,53 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Connection	I.D. 9
DN	5
Flow rate	310 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	46.5 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK557
Page No. SK	SK039
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface

Spring  
 Valve body

Stainless steel  
 Brass with a bare metal surface

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107498	I.D. 9	6,53 € / Stk
107496	I.D. 4	6,32 € / Stk
107497	I.D. 6	6,32 € / Stk

## More Pictures

