

Datasheet for: 107698


Closing nipple locking on both sides, Brass, G 1/8 IT, I.D. 4.3

Closing nipple locking on both sides, Bright brass, G 1/8 IT, I.D. 4.3. Operating pressure max. 250 bar, Temp. -20 °C to 100 °C . Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series. Areas of application: machine and plant engineering, manufacturing industry, chemical / pharmaceutical industry, automotive, food technology.

Type number	246.51
Article number	107698
EAN/barcode	 4047322061421
Your price	11,61 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 1/8 IT
DN	4.3
Flow rate (air)	440 l/min
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	29.5 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	250 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	Referred to medium temp. of 50 °C, static working pressure
Page No.	HK602
Page No. SK	SK085
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve	Brass with a bare metal surface

a/f

14 mm

Variants

Article number	Connection	Flow rate (air)	DN	Max. operating pressure	a/f	Price
107698	G 1/8 IT	440 l/min	4.3	250 bar	14 mm	11,61 € / Stk
107699	G 1/4 IT	840 l/min	6.3	200 bar	19 mm	11,99 € / Stk
107700	G 3/8 IT	1280 l/min	7.5	200 bar	22 mm	15,56 € / Stk
107701	G 1/2 IT	1950 l/min	11	150 bar	27 mm	19,82 € / Stk
107702	G 3/4 IT	4500 l/min	13	100 bar	36 mm	31,82 € / Stk

More Pictures

