


Datasheet for: 107959


Tempered coupling DN 9, ET, Blocking valve, M16x1.5 straight

Tempered coupling DN 9, Exterior thread, Blocking valve, Brass, M16x1.5 straight, Operating pressure max. 15 bar . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.21
Article number	107959
EAN/barcode	 4047322258760
Your price	15,61 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connecting thread	M16x1.5 straight
Length	52.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK617
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
a/f	22 mm

Variants

<i>Article number</i>	<i>Connecting thread</i>	<i>a/f</i>	<i>Price</i>
107959	M16x1.5 straight	22 mm	15,61 € / Stk
107961	G 1/2 straight	21 mm	16,89 € / Stk
107962	G 3/8 45°	22 mm	20,51 € / Stk
107960	G 3/8 straight	22 mm	15,15 € / Stk
107965	M16x1.5 90°	22 mm	20,51 € / Stk
107964	G 3/8 90°	22 mm	20,51 € / Stk
107963	M16x1.5 45°	22 mm	20,51 € / Stk