


## Datasheet for: 116048


**3/2-way valve, Pneumatic, »3A«, bistable, G 1/8**

3/2-way valve, Pneumatic, »3A«, bistable, G 1/8, Operating pressure 1.5 - 8 bar, Temperature range max. 70 °C . 3/2-way pilot valves - Pneumatic -

Type number	516.3002
Article number	116048
EAN/barcode	 4047322309493
Your price	32,35 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8
Control air port	G 1/8
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement function	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Max. operating pressure	3/2
Max. temperature range	8 bar
Min. operating pressure	70 °C
Operation	1.5 bar
Page No.	Bistable
Page No. AS	HK463
Size	AS083
Symbol	200
Valve body	26
	Aluminium alloy

## Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116048	G 1/8	G 1/8	750 l/min	200	32,35 € / Stk
116050	G 1/4	G 1/4	1300 l/min	300	39,82 € / Stk
116046	M5	M5	300 l/min	100	31,31 € / Stk
116047	G 1/8	G 1/8	500 l/min	100	31,31 € / Stk
116049	G 1/4	G 1/4	850 l/min	200	32,35 € / Stk
116051	G 3/8	G 3/8	1500 l/min	300	39,82 € / Stk

## More Pictures

