


Datasheet for: 115991


3/2-way valve, Manually actuated, »M3«, Toggle lever, NC, G 1/4

3/2-way valve, Manually actuated, »M3«, Toggle lever, NC, bistable, G 1/4, Operating pressure - 10 bar, Temp. -20 °C to 70 °C . 3/2-way valves - Manually operated, for panel mounting -

Type number	515.3001
Article number	115991
EAN/barcode	 4047322311366
Your price	39,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Exhaust connection	G 1/4
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Lever/switch colour	black
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Bistable
Page No.	HK453
Page No. AS	AS078
Symbol	4
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Price
115991	G 1/4	G 1/4	550 l/min	39,46 € / Stk
115990	G 1/8	G 1/8	450 l/min	39,46 € / Stk

More Pictures

