

Datasheet for: 116000



**5/2-way valve, manual »M5« Push button, monostable, G 1/8**

5/2-way valve, manual »M5« Push button, monostable, Control panel integration, G 1/8, Operating pre. 0-10 bar, Temp. -20°C to 70°C . 5/2-way valves - Manually operated, for panel mounting -

Type number 515.4100

Article number 116000

EAN/barcode



4047322311663

Your price 39,46 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	450 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Lever/switch colour	black
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Monostable
Page No.	HK457
Page No. AS	AS080
Symbol	1
Valve body	Aluminium alloy

## Variants

Article number	Connection	Flow rate	Lever/switch colour	Price
116000	G 1/8	450 l/min	black	39,46 € / Stk
116001	G 1/8	450 l/min	red	39,46 € / Stk
116005	G 1/4	550 l/min	green	52,96 € / Stk
116003	G 1/4	550 l/min	black	52,96 € / Stk
116002	G 1/8	450 l/min	green	39,46 € / Stk
116004	G 1/4	550 l/min	red	52,96 € / Stk

## More Pictures

