


Datasheet for: 116001


5/2-way valve, manual »M5« Push button, monostable, G 1/8

5/2-way valve, manual »M5« Push button, monostable, Control panel integration, G 1/8, Operating pre. 0-10 bar, Temp. -20°C to 70°C . 5/2-way valves - Manually operated, for panel mounting -

Type number	515.4101
Article number	116001
EAN/barcode	 4047322311670
Your price	39,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	450 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Lever/switch colour	red
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Monostable
Page No.	HK457
Page No. AS	AS080
Symbol	1
Valve body	Aluminium alloy

Variants

<i>Article number</i>	<i>Connection</i>	<i>Flow rate</i>	<i>Lever/switch colour</i>	<i>Price</i>
116001	G 1/8	450 l/min	red	39,46 € / Stk
116000	G 1/8	450 l/min	black	39,46 € / Stk
116005	G 1/4	550 l/min	green	52,96 € / Stk
116003	G 1/4	550 l/min	black	52,96 € / Stk
116002	G 1/8	450 l/min	green	39,46 € / Stk
116004	G 1/4	550 l/min	red	52,96 € / Stk

More Pictures

