


Datasheet for: 116018


3/2-way valve, manual »M3« Rotating handle, NC, monostable, G 1/8

3/2-way valve, manual »M3«, Rotating handle, short, NC, monostable, Control panel integration, G 1/8, Operating pressure 0-10 bar . 3/2-way valves - Manually operated, for panel mounting -

Type number	515.6000
Article number	116018
EAN/barcode	 4047322311502
Your price	39,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	450 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Lever/switch colour	black
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Monostable
Page No.	HK454
Page No. AS	AS078
Symbol	3
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Lever/switch colour	Price
116018	G 1/8	G 1/8	450 l/min	black	39,46 € / Stk
116020	G 1/8	G 1/8	450 l/min	green	39,46 € / Stk
116022	G 1/4	G 1/4	550 l/min	red	39,46 € / Stk
116023	G 1/4	G 1/4	550 l/min	green	39,46 € / Stk
116019	G 1/8	G 1/8	450 l/min	red	39,46 € / Stk
116021	G 1/4	G 1/4	550 l/min	black	39,46 € / Stk

More Pictures

