


Datasheet for: 100284


Ball valve 3/2-way »FUTURA«, lockable, Size 1, G 3/8

Ball valve 3/2-way »FUTURA«, lockable, Size 1, G 3/8, Exhaust G 1/4, Input pressure max. 16 bar, Temperature -10 °C to 50 °C . Lockable ball valve, 3/2-way type including silencer, mechanically operated. Rotary switch can be turned 90°, with indication of positions: Horizontal: Input closed - outlet exhausted Vertical: Flow open - exhaust closed Exhaust air can be collected.

| | |
|----------------|--|
| Type number | FU 952 |
| Article number | 100284 |
| EAN/barcode |  4047322191258 |
| Your price | 32,41 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|--|
| A | 52.0 mm |
| B | 87.5 mm |
| C | 54.5 mm |
| Connecting thread | Material: Die-cast zinc |
| Exhaust air | G 1/4 |
| Flow rate | 1900 l/min |
| Flow rate measurement | At P ₂ = 6 bar and pressure drop $\Delta_p = 1$ bar |
| Housing | PA66 GF60 |
| Max. input pressure | 16 bar |
| Max. temperature range | 50 °C |
| Medium | Compressed air, neutral gases |
| Min. temperature range | -10 °C |
| Page No. | HK054 |
| Page No. SF | SF018 |
| Series | FUTURA |
| Size | 1 |
| Thread | G 3/8 |

Variants

| Article number | Thread | Exhaust air | Flow rate | Size | Price |
|----------------|--------|-------------|-------------|------|----------------|
| 100284 | G 3/8 | G 1/4 | 1900 l/min | 1 | 32,41 € / Stk |
| 100283 | G 1/4 | G 1/4 | 1900 l/min | 1 | 32,41 € / Stk |
| 100285 | G 3/8 | G 1/2 | 14000 l/min | 2 | 47,76 € / Stk |
| 100286 | G 1/2 | G 1/2 | 14000 l/min | 2 | 47,76 € / Stk |
| 100288 | G 1 | G 3/4 | 25000 l/min | 4 | 107,74 € / Stk |
| 100287 | G 3/4 | G 3/4 | 25000 l/min | 4 | 107,74 € / Stk |

More Pictures

