


Datasheet for: 103315


Rectangular ball valve, nickel-plated brass, IT/ET, R/Rp 1

Rectangular ball valve, nickel-plated brass, IT/ET, Operating temp. -15 °C to 100 °C/60 °C gas, R/Rp 1, PN max. 40 bar/ 5 bar gas .

Type number	350.305
Article number	103315
EAN/barcode	 4047322075893
Your price	39,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	56.0 mm
Applications	Gas, compressed air, water, oil
B	50.0 mm
Ball seal	PTFE
Butterfly handle	Aluminium, painted yellow
C Ø	48.0 mm
DN	25.0
DVGW approval	DIN EN 331:2013-05
E	51.0 mm
F	46.0 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
Operating pressure	max. 5 bar (MOP 5) gas, max. 40 bar liquids
Operating temperature	-15 °C to 60 °C for gas, -15 °C to 100 °C for liquids
Page No.	HK290
Standard thread	R or RP thread acc. to ISO 7-1
Stem seal	NBR
Thread	R/Rp 1
Thread material	Brass with a bare metal surface

Variants

Article number	Thread	DN	Price
103315	R/Rp 1	25.0	39,72 € / Stk
103313	R/Rp 1/2	15.0	19,10 € / Stk
103314	R/Rp 3/4	20.0	28,89 € / Stk

More Pictures

