


Datasheet for: 115953


3/2-way valve, Mechanically actuated, »M3«, Tappet, NC, G 1/4

3/2-way valve, Mechanically actuated, »M3«, Tappet, NC, G 1/4, Operating pressure - 10 bar, Temperature range -20 °C to 70 °C . 3/2-way valves - Mechanically operated -

Type number	511.1001
Article number	115953
EAN/barcode	 4047322309196
Your price	32,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Exhaust connection	G 1/4
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Page No.	HK449
Page No. AS	AS076
Symbol	1
Valve body	Aluminium alloy

Variants

<i>Article number</i>	<i>Connection</i>	<i>Exhaust connection</i>	<i>Flow rate</i>	<i>Price</i>
115953	G 1/4	G 1/4	550 l/min	32,58 € / Stk
115952	G 1/8	G 1/8	450 l/min	32,58 € / Stk

More Pictures

