


Datasheet for: 115978


5/2-way valve, Push button actuation, »3L« G 1/8

5/2-way valve, Push button actuation, »3L« Control panel integration, G 1/8, Operating pressure 0-8 bar, Temp. range -20°C to 70°C . The hand lever latches when pushed or pulled.

Type number	514.4002
Article number	115978
EAN/barcode	 4047322312059
Your price	32,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Page No.	HK462
Page No. AS	AS082
Size	200
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
115978	G 1/8	G 1/8	750 l/min	200	32,58 € / Stk
115981	G 3/8	G 1/4	1500 l/min	300	46,32 € / Stk
115977	G 1/8	G 1/8	500 l/min	100	27,71 € / Stk
115979	G 1/4	G 1/8	850 l/min	200	32,58 € / Stk
115980	G 1/4	G 1/4	1300 l/min	300	46,32 € / Stk

More Pictures

