


Datasheet for: 116050


3/2-way valve, Pneumatic, »3A«, bistable, G 1/4

3/2-way valve, Pneumatic, »3A«, bistable, G 1/4, Operating pressure 1.5 - 8 bar, Temperature range max. 70 °C . 3/2-way pilot valves - Pneumatic -

Type number	516.3004
Article number	116050
EAN/barcode	 4047322309516
Your price	39,82 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Control air port	G 1/8
Exhaust connection	G 1/4
Flow rate	1300 l/min
Flow rate measurement function	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Bistable
Page No.	HK463
Page No. AS	AS083
Size	300
Symbol	26
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116050	G 1/4	G 1/4	1300 l/min	300	39,82 € / Stk
116046	M5	M5	300 l/min	100	31,31 € / Stk
116048	G 1/8	G 1/8	750 l/min	200	32,35 € / Stk
116047	G 1/8	G 1/8	500 l/min	100	31,31 € / Stk
116049	G 1/4	G 1/4	850 l/min	200	32,35 € / Stk
116051	G 3/8	G 3/8	1500 l/min	300	39,82 € / Stk

More Pictures

