

## Datasheet for: 108424


**Flow valve, ET top, Aluminium, Ball seat valve**

Flow valve, ET top, Required suction capacity  $p_u = 0.3$  bar 1.2 l/min,  $p_u = -0.6$  bar 1.3, Aluminium, Ball seat valve . Check valves close the vacuum line if the suction pad is not covered, thus maintaining the vacuum. The valves are protected against dirt by a replaceable sieve. This valve series is suitable for all suction pads in our standard range.

Type number	SVK 515
Article number	108424
EAN/barcode	 4047322201063
Your price	16,00 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Housing	Aluminium
Length	15.5 mm
Max. flow rate when blowing off	80 l/min
Page No.	WEB
Required evac. rate for $p_u = -0.3$ bar	1.2 l/min
Required evac. rate for $p_u = -0.6$ bar	1.3 l/min
Thread 1	M5 ET
Thread 2	M5 IT
Type of construction	Ball seat valve (ball in brass seat)
Weight	2.2 g

## Variants

Article number	Thread 1	Thread 2	Max. flow rate when blowing off	Required evac. rate for pu = -0.6 bar	Required evac. rate for pu = -0.3 bar	Price
108424	M5 ET	M5 IT	80 l/min	1.3 l/min	1.2 l/min	16,00 € / Stk
108425	G 1/8 ET	G 1/8 IT	310 l/min	2.5 l/min	2.3 l/min	22,92 € / Stk
108426	G 1/4 ET	G 1/4 IT	340 l/min	3.4 l/min	2.9 l/min	25,85 € / Stk
108427	G 1/2 ET	G 1/2 IT	790 l/min	9.0 l/min	8.1 l/min	40,64 € / Stk