


Datasheet for: 113177


Fitting 331, IT/ET, Rp/R 2, NBR seal, black malleable cast iron

Fitting 331, flat sealing, IT/ET, Rp/R 2, NBR seal, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galva. . Maximum temperature and maximum operating pressure should not occur at the same time! Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.

Type number	TFV 331-20-D
Article number	113177
EAN/barcode	 4047322384117
Your price	20,59 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK863
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp/R 2
Thread	

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113177	Rp/R 2	20,59 € / Stk
113170	Rp/R 1/4	16,89 € / Stk
113172	Rp/R 1/2	5,01 € / Stk
113176	Rp/R 1 1/2	13,35 € / Stk
113174	Rp/R 1	7,90 € / Stk
113175	Rp/R 1 1/4	10,78 € / Stk
113173	Rp/R 3/4	6,39 € / Stk
113171	Rp/R 3/8	6,56 € / Stk
113178	Rp/R 2 1/2	47,01 € / Stk