

Datasheet for: 141525

Quick-connect coupling I.D. 7.8, Steel, Hose connection 12x9



Quick-connect coupling I.D. 7.8, Steel, Hose connection 12x9, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . Single-sided blocking, high quality and robust quick connect coupling for high flow values. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.

Type number	244.92-1-E
Article number	141525
EAN/barcode	 4047322568173
Your price	16,00 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	Hose connection 12x9
DN	7.8
Flow rate	2000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Galvanised steel
Length	64.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK549
Page No. SK	SK031
Sealant	NBR

Sleeve
 Spring
 Threaded piece
 Valve
 a/f

Galvanised steel
 Stainless steel
 Galvanised steel
 Die-cast zinc (zamac)
 19 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>Price</i>
141525	Hose connection 12x9	64.0 mm	16,00 € / Stk
141524	Hose connection 10x8	64.0 mm	16,00 € / Stk
141523	Hose connection 8x6	61.0 mm	16,00 € / Stk

More Pictures

