

Datasheet for: 136781


Push-in L-connector »metallica«, for hose exterior Ø 16 mm

Push-in L-connector »metallica«, for hose exterior Ø 16 mm, Working pressure max. 16 bar, Operating temperature -20 °C to 150 °C . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	848.016
Article number	136781
EAN/barcode	 4047322508285
Your price	32,99 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	16 mm
L1	33.0 mm
L2	33.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK716
Series	metallica
Sleeve	Nickel-plated brass

Variants

Article number	For tube O.D.	Price
136781	16 mm	32,99 € / Stk

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
108982	4 mm	3,09 € / Stk
108985	10 mm	5,00 € / Stk
108984	8 mm	3,74 € / Stk
108983	6 mm	3,25 € / Stk
108987	14 mm	8,35 € / Stk
108986	12 mm	6,31 € / Stk

More Pictures

