

## Datasheet for: 107256


**Distributor with 2 quick-connect couplings I.D. 7.2, G 1/4 ET**

Distributor with 2 quick-connect couplings I.D. 7.2, Bright brass, G 1/4 ET, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . 1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Type number	245.31
Article number	107256
EAN/barcode	 4047322061131
Your price	16,19 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Comprising distributor	Brass with a bare metal surface, G 3/8 IT
Connection	G 1/4 ET
Couplings	DN 7.2, brass with a bare metal surface, G 3/8 ET
Height	85.0 mm
Housing	Brass with a bare metal surface
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	35 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK534
Page No. SK	SK019
Sealant	Industrial adhesives, medium strength
Securing	Industrial adhesives, medium strength
Width	92.0 mm

## Variants

Article number	Connection	Comprising distributor	Couplings	Price
107256	G 1/4 ET	Brass with a bare metal surface, G 3/8 IT DN 7.2, brass with a bare metal surface, G 3/8 ET	16,19 €	
107257	G 3/8 ET	Brass with a bare metal surface, G 3/8 IT DN 7.2, brass with a bare metal surface, G 3/8 ET	16,19 €	
107258	G 1/2 ET	Brass with a bare metal surface, G 1/2 IT DN 7.2, brass with a bare metal surface, G 1/2 ET	19,81 €	

## More Pictures

