


Datasheet for: 107786



**GEKA threaded piece, 360° rotating, bright brass, G 1 interior**

GEKA threaded piece, 360° rotating, bright brass, G 1 interior, Operating pressure max. 40 bar, Medium/ambient temp. -10°C to 90°C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 213
Article number	107786
EAN/barcode	 4047322133197
Your price	21,21 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1 IT
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK607
Sealant	NBR

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107786	G 1 IT	21,21 € / Stk
107784	G 1/2 IT	15,37 € / Stk
107785	G 3/4 IT	15,84 € / Stk